




Zinc - Copper Lug

**Images**



[Download Photo Image](#)

[Download Dimensional Image](#)

**Dimensional Data**

| Catalog Number | Dimension A | Dimension B | Dimension C |
|----------------|-------------|-------------|-------------|
| 351-DC         | 1           | 1-1/4       |             |
| 352-DC         | 1-1/4       | 1-3/8       |             |
| 353-DC         | 1-1/2       | 1-1/2       |             |
| 354-DC         | 1-7/8       | 1-5/8       |             |
| 355-DC         | 2-1/8       | 2           |             |
| 356-DC         | 2-5/8       | 2-1/4       |             |
| 357-DC         | 3-3/16      | 2-7/8       |             |
| 358-DC         | 3-7/8       | 3-1/4       |             |
| 359-DC         | 4-1/4       | 3-1/2       |             |
| 360-DC         | 4-7/8       | 3-3/4       |             |

**Application**

Used with locknut to terminate service conduit to cabinet. Solid copper lugs provides high conductivity with lower heat rise than conventional solderless lugs. Plastic metaliner rated 150 degree C.

**Product Information**

| Catalog Number | Trade Size | UPC Item Number |
|----------------|------------|-----------------|
| 351-DC         | 1/2"       | 09351           |
| 352-DC         | 3/4"       | 09352           |
| 353-DC         | 1"         | 09353           |
| 354-DC         | 1-1/4"     | 09354           |
| 355-DC         | 1-1/2"     | 09355           |
| 356-DC         | 2"         | 09356           |
| 357-DC         | 2-1/2"     | 09357           |
| 358-DC         | 3"         | 09358           |
| 359-DC         | 3-1/2"     | 09359           |
| 360-DC         | 4"         | 09360           |

Material: Zinc Die Cast  
Finish: Ball burnished, mirror smooth

**Certifications & Codes:**

|                               |           |
|-------------------------------|-----------|
| Federal Specification Number: | A-A-50553 |
| NEMA Standard:                | FB-1      |
| UL File Number:               | E20412    |
| UL Standard:                  | UL-514B   |
| UNSPSC:                       | 39121312  |

**Catalog ID:** 351-DC

**UPC Number:** 781747093516

**Description:** Bushing, Grounding, Insulated, Copper Lugs, Zinc Die Cast, Size 1/2 Inch

**Application:** Used with locknut to terminate service conduit to cabinet. Solid copper lugs provides high conductivity with lower heat rise than conventional solderless lugs. Plastic metaliner rated 150 degree C.

**Trade Size:** 1/2"

**Country of Manufacture:** USA